

LED 2x100W CW/WW Blinder

MAIN FEATURES

- 1. 2x100W dual white LED blinder
- 2. CRI90, 3200K warm white+6500K cold white
- 3. Outer RGB LED ring and inner RGB LED ring



TECHNICAL SPECIFICATIONS

ELECTRICAL

- Input power: AC100-240V
- Power frequency: 50/60Hz
- Power: 180W

LIGHT SOURCE

- Source: 2*100W dual white LED
72pcs 0.2W RGB 3in1 LED
- Average lifespan: 50,000 hours

COLOR SYSTEM

- Color : 3200K WW+6500K CW;RGB

ELECTRONICS

- Linear dimming: 0-100% Linear Dimmer
- Strobe: 1-25Hz

OPTICS

- Beam Angle:90°

DYNAMIC EFFECTS

- Built-in programs and strobe effects with adjustable speed
- Orientation of the four eyes adjustable
- One inner and outer RGB halo ring with macro effects

CONTROL

- DMX channel:10/26CH
- DMX connector: DMX 3-Pin XLR input/output
- Power connector: Power Con input/output
- Control mode:DMX/Master-Slave/Auto/Sound
- LED display

PHYSICAL

- IP Rating:IP20
- Housing color: black
- Working ambient temp.: -10°C to 40°C (-14°F to 104°F)

PHOTOMETRICS DIAGRAM

