

LED 4x100W CW/WW Blinder

MAIN FEATURES

- 1. 4x100W COB CW+WW, 96PCS 0.2W RGB LED
- 2. Control mode: DMX/ AUTO/SOUND/MASTER SLAVE
- 3. Beam angle: 45°



TECHNICAL SPECIFICATIONS

ELECTRICAL

- Input power: AC100-240V
- Power frequency: 50/60Hz
- Power: 330W

LIGHT SOURCE

- Source: 100W*4 COB CW+WW
96PCS 0.2W RGB LED
- Average lifespan: 50,000 hours

COLOR SYSTEM

- Color : 6500K CW+3200K WW ;RGB

ELECTRONICS

- Linear dimming: 0-100% Linear Dimmer
- Strobe: 1-25Hz

OPTICS

- Beam Angle:45°

DYNAMIC EFFECTS

- Built-in programs and strobe effects with adjustable speed
- Orientation of the four eyes adjustable in columns of two
- One outer RGB halo ring with macro effects

CONTROL

- DMX channel:7/17CH
- DMX connector:3-Pin XLR input/output
- Power connector: PowerCon input and output
- Control mode:DMX/Master-Slave/Auto/Sound
- LED display

PHYSICAL

- IP Rating:20
- Housing color: black
- Working ambient temp.: -10°C to 40°C (-14°F to 104°F)

PHOTOMETRICS DIAGRAM

